

GAE

GREAT AMERICAN ELECTROINCS

BLY-38/C3-12

Silicon NPN power VHF/UHF transistor BLY-38/C3-12 is designed for large signal amplifier and multiplier applications in portable and land mobile FM and AM equipment.

Output Power: 2 Watt
Frequency Range: 200-400 Mhz
Voltage: 12.6 V
Package Type: 8/32 Helicopter
Common Emitter Configuration
Individual Emitter Resistors
Aluminum Metalization

Electrical Characteristics ($T_{CASE}=40^{\circ}C$)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
P_{out}	$f_o = 320 \text{ Mhz}/V_{cc}=12.6V/P_{IN}=0.32W$	2			W
G_p	$f_o = 320 \text{ Mhz}/V_{cc}=12.6V/P_{out}=2W$	8			dB
λ_C	$f_o = 320 \text{ Mhz}/V_{cc}=12.6V/P_{out}=2W$	60	65		%

ABSOLUTE MAXIMUM RATINGS ($T_{CASE} = 25^{\circ}C$)

SYMBOL	PARAMETERS	VALUE	UNIT
V_{CER}	Collector-Emitter Voltage $R_{EB} \leq 100\Omega$	36	V
V_{EBO}	Emitter-Base Voltage	4	V
I_c	Continuous Collector Current	0.5	A
P_C	Collector Power Dissipation	5.5*	W
T_j	Junction Temperature	150	$^{\circ}C$
$R_{th(j-c)}$	Junction-Case Thermal Resistance	20	$^{\circ}C/W$

*For Dynamic Operation $T_{CASE} = 40^{\circ}C$

■ 3288292 0000042 499 ■